



DPDK

DATA PLANE DEVELOPMENT KIT

Testpmd Application User Guide

Release 16.11.11

Nov 15, 2019

1	Introduction	1
2	Compiling the Application	2
3	Running the Application	3
3.1	EAL Command-line Options	3
3.2	Testpmd Command-line Options	5
4	Testpmd Runtime Functions	10
4.1	Help Functions	10
4.2	Control Functions	11
4.2.1	start	11
4.2.2	start tx_first	11
4.2.3	stop	11
4.2.4	quit	11
4.3	Display Functions	11
4.3.1	show port	11
4.3.2	show port rss reta	12
4.3.3	show port rss-hash	12
4.3.4	clear port	12
4.3.5	show (rxq txq)	13
4.3.6	show config	13
4.3.7	set fwd	13
4.3.8	read rxd	14
4.3.9	read txd	14
4.4	Configuration Functions	14
4.4.1	set default	15
4.4.2	set verbose	15
4.4.3	set nbport	15
4.4.4	set nbcore	15
4.4.5	set coremask	15
4.4.6	set portmask	15
4.4.7	set burst	16
4.4.8	set txpkts	16
4.4.9	set txsplit	16
4.4.10	set corelist	16
4.4.11	set portlist	17
4.4.12	set tx loopback	17
4.4.13	set drop enable	17

4.4.14	set split drop enable (for VF)	17
4.4.15	set mac antispoof (for VF)	17
4.4.16	vlan set strip	17
4.4.17	vlan set stripq	17
4.4.18	vlan set stripq (for VF)	18
4.4.19	vlan set insert (for VF)	18
4.4.20	vlan set antispoof (for VF)	18
4.4.21	vlan set filter	18
4.4.22	vlan set qinq	18
4.4.23	vlan set tpid	18
4.4.24	rx_vlan add	18
4.4.25	rx_vlan rm	19
4.4.26	rx_vlan add (for VF)	19
4.4.27	rx_vlan rm (for VF)	19
4.4.28	tunnel_filter add	19
4.4.29	tunnel_filter remove	20
4.4.30	rx_vxlan_port add	20
4.4.31	rx_vxlan_port remove	20
4.4.32	tx_vlan set	20
4.4.33	tx_vlan set pvid	20
4.4.34	tx_vlan reset	20
4.4.35	csum set	20
4.4.36	csum parse-tunnel	21
4.4.37	csum show	21
4.4.38	tso set	21
4.4.39	tso show	22
4.4.40	mac_addr add	22
4.4.41	mac_addr remove	22
4.4.42	mac_addr add (for VF)	22
4.4.43	mac_addr set (for VF)	22
4.4.44	set port-uta	22
4.4.45	set promisc	22
4.4.46	set allmulti	22
4.4.47	set flow_ctrl rx	23
4.4.48	set pfc_ctrl rx	23
4.4.49	set stat_qmap	23
4.4.50	set port - rx/tx (for VF)	23
4.4.51	set port - mac address filter (for VF)	24
4.4.52	set port - rx mode(for VF)	24
4.4.53	set port - tx_rate (for Queue)	24
4.4.54	set port - tx_rate (for VF)	24
4.4.55	set port - mirror rule	24
4.4.56	reset port - mirror rule	24
4.4.57	set flush_rx	25
4.4.58	set bypass mode	25
4.4.59	set bypass event	25
4.4.60	set bypass timeout	25
4.4.61	show bypass config	25
4.4.62	set link up	25
4.4.63	set link down	26
4.4.64	E-tag set	26

4.5	Port Functions	26
4.5.1	port attach	26
4.5.2	port detach	27
4.5.3	port start	28
4.5.4	port stop	28
4.5.5	port close	28
4.5.6	port start/stop queue	29
4.5.7	port config - speed	29
4.5.8	port config - queues/descriptors	29
4.5.9	port config - max-pkt-len	29
4.5.10	port config - CRC Strip	29
4.5.11	port config - scatter	29
4.5.12	port config - TX queue flags	30
4.5.13	port config - RX Checksum	30
4.5.14	port config - VLAN	30
4.5.15	port config - VLAN filter	30
4.5.16	port config - VLAN strip	30
4.5.17	port config - VLAN extend	30
4.5.18	port config - Drop Packets	31
4.5.19	port config - RSS	31
4.5.20	port config - RSS Reta	31
4.5.21	port config - DCB	31
4.5.22	port config - Burst	31
4.5.23	port config - Threshold	31
4.5.24	port config - E-tag	32
4.6	Link Bonding Functions	32
4.6.1	create bonded device	32
4.6.2	add bonding slave	32
4.6.3	remove bonding slave	32
4.6.4	set bonding mode	33
4.6.5	set bonding primary	33
4.6.6	set bonding mac	33
4.6.7	set bonding xmit_balance_policy	33
4.6.8	set bonding mon_period	33
4.6.9	show bonding config	34
4.7	Register Functions	34
4.7.1	read reg	34
4.7.2	read regfield	34
4.7.3	read regbit	34
4.7.4	write reg	35
4.7.5	write regfield	35
4.7.6	write regbit	35
4.8	Filter Functions	35
4.8.1	ethertype_filter	35
4.8.2	2tuple_filter	36
4.8.3	5tuple_filter	36
4.8.4	syn_filter	37
4.8.5	flex_filter	37
4.8.6	flow_director_filter	38
4.8.7	flush_flow_director	39
4.8.8	flow_director_mask	39

4.8.9	flow_director_flex_mask	40
4.8.10	flow_director_flex_payload	40
4.8.11	get_sym_hash_ena_per_port	40
4.8.12	set_sym_hash_ena_per_port	40
4.8.13	get_hash_global_config	41
4.8.14	set_hash_global_config	41
4.8.15	set_hash_input_set	41
4.8.16	set_fdir_input_set	41
4.8.17	global_config	42

INTRODUCTION

This document is a user guide for the `testpmd` example application that is shipped as part of the Data Plane Development Kit.

The `testpmd` application can be used to test the DPDK in a packet forwarding mode and also to access NIC hardware features such as Flow Director. It also serves as an example of how to build a more fully-featured application using the DPDK SDK.

The guide shows how to build and run the `testpmd` application and how to configure the application from the command line and the run-time environment.

COMPILING THE APPLICATION

The `testpmd` application is compiled as part of the main compilation of the DPDK libraries and tools. Refer to the DPDK Getting Started Guides for details. The basic compilation steps are:

1. Set the required environmental variables and go to the source directory:

```
export RTE_SDK=/path/to/rte_sdk
cd $RTE_SDK
```

2. Set the compilation target. For example:

```
export RTE_TARGET=x86_64-native-linuxapp-gcc
```

3. Build the application:

```
make install T=$RTE_TARGET
```

The compiled application will be located at:

```
$RTE_SDK/$RTE_TARGET/app/testpmd
```

RUNNING THE APPLICATION

3.1 EAL Command-line Options

The following are the EAL command-line options that can be used in conjunction with the `testpmd`, or any other DPDK application. See the DPDK Getting Started Guides for more information on these options.

- `-c COREMASK`

Set the hexadecimal bitmask of the cores to run on.

- `-l CORELIST`

List of cores to run on

The argument format is `<c1>[-c2] [, c3[-c4], ...]` where `c1`, `c2`, etc are core indexes between 0 and 128.

- `--lcores COREMAP`

Map lcore set to physical cpu set

The argument format is:

```
<lcores[@cpus]>[<,lcores[@cpus]>...]
```

Lcore and CPU lists are grouped by `(and)` Within the group. The `-` character is used as a range separator and `,` is used as a single number separator. The grouping `()` can be omitted for single element group. The `@` can be omitted if `cpus` and `lcores` have the same value.

- `--master-lcore ID`

Core ID that is used as master.

- `-n NUM`

Set the number of memory channels to use.

- `-b, --pci-blacklist domain:bus:devid.func`

Blacklist a PCI device to prevent EAL from using it. Multiple `-b` options are allowed.

- `-d LIB.so`

Load an external driver. Multiple `-d` options are allowed.

- `-w, --pci-whitelist domain:bus:devid:func`

Add a PCI device in white list.

- `-m MB`
Memory to allocate. See also `--socket-mem`.
- `-r NUM`
Set the number of memory ranks (auto-detected by default).
- `-v`
Display the version information on startup.
- `--xen-dom0`
Support application running on Xen Domain0 without hugetlbfs.
- `--syslog`
Set the syslog facility.
- `--socket-mem`
Set the memory to allocate on specific sockets (use comma separated values).
- `--huge-dir`
Specify the directory where the hugetlbfs is mounted.
- `--proc-type`
Set the type of the current process.
- `--file-prefix`
Prefix for hugepage filenames.
- `-vmware-tsc-map`
Use VMware TSC map instead of native RDTSC.
- `--vdev`
Add a virtual device using the format:

```
<driver><id>[,key=val, ...]
```


For example:

```
--vdev 'net_pcap0,rx_pcap=input.pcap,tx_pcap=output.pcap'
```
- `--base-virtaddr`
Specify base virtual address.
- `--create-uio-dev`
Create `/dev/uioX` (usually done by hotplug).
- `--no-shconf`
No shared config (mmap-ed files).
- `--no-pci`
Disable pci.
- `--no-hpet`
Disable hpet.

- `--no-huge`
Use malloc instead of hugeblfs.

3.2 Testpmd Command-line Options

The following are the command-line options for the testpmd applications. They must be separated from the EAL options, shown in the previous section, with a `--` separator:

```
sudo ./testpmd -c 0xF -n 4 -- -i --portmask=0x1 --nb-cores=2
```

The commandline options are:

- `-i, --interactive`
Run testpmd in interactive mode. In this mode, the testpmd starts with a prompt that can be used to start and stop forwarding, configure the application and display stats on the current packet processing session. See *Testpmd Runtime Functions* for more details.

In non-interactive mode, the application starts with the configuration specified on the command-line and immediately enters forwarding mode.
- `-h, --help`
Display a help message and quit.
- `-a, --auto-start`
Start forwarding on initialization.
- `--nb-cores=N`
Set the number of forwarding cores, where $1 \leq N \leq$ “number of cores” or `CONFIG_RTE_MAX_LCORE` from the configuration file. The default value is 1.
- `--nb-ports=N`
Set the number of forwarding ports, where $1 \leq N \leq$ “number of ports” on the board or `CONFIG_RTE_MAX_ETHPORTS` from the configuration file. The default value is the number of ports on the board.
- `--coremask=0xXX`
Set the hexadecimal bitmask of the cores running the packet forwarding test. The master lcore is reserved for command line parsing only and cannot be masked on for packet forwarding.
- `--portmask=0xXX`
Set the hexadecimal bitmask of the ports used by the packet forwarding test.
- `--numa`
Enable NUMA-aware allocation of RX/TX rings and of RX memory buffers (mbufs).
- `--port-numa-config=(port, socket) [, (port, socket)]`
Specify the socket on which the memory pool to be used by the port will be allocated.
- `--ring-numa-config=(port, flag, socket) [, (port, flag, socket)]`

Specify the socket on which the TX/RX rings for the port will be allocated. Where flag is 1 for RX, 2 for TX, and 3 for RX and TX.

- `--socket-num=N`

Set the socket from which all memory is allocated in NUMA mode, where $0 \leq N <$ number of sockets on the board.

- `--mbuf-size=N`

Set the data size of the mbufs used to N bytes, where $N < 65536$. The default value is 2048.

- `--total-num-mbufs=N`

Set the number of mbufs to be allocated in the mbuf pools, where $N > 1024$.

- `--max-pkt-len=N`

Set the maximum packet size to N bytes, where $N \geq 64$. The default value is 1518.

- `--eth-peers-configfile=name`

Use a configuration file containing the Ethernet addresses of the peer ports. The configuration file should contain the Ethernet addresses on separate lines:

```
XX:XX:XX:XX:XX:01
XX:XX:XX:XX:XX:02
...
```

- `--eth-peer=N, XX:XX:XX:XX:XX:XX`

Set the MAC address `XX:XX:XX:XX:XX:XX` of the peer port N, where $0 \leq N <$ `CONFIG_RTE_MAX_ETHPORTS` from the configuration file.

- `--pkt-filter-mode=mode`

Set Flow Director mode where mode is either `none` (the default), `signature` or `perfect`. See [flow_director_filter](#) for more details.

- `--pkt-filter-report-hash=mode`

Set Flow Director hash match reporting mode where mode is `none`, `match` (the default) or `always`.

- `--pkt-filter-size=N`

Set Flow Director allocated memory size, where N is 64K, 128K or 256K. Sizes are in kilobytes. The default is 64.

- `--pkt-filter-flexbytes-offset=N`

Set the flexbytes offset. The offset is defined in words (not bytes) counted from the first byte of the destination Ethernet MAC address, where $0 \leq N \leq 32$. The default value is 0x6.

- `--pkt-filter-drop-queue=N`

Set the drop-queue. In perfect filter mode, when a rule is added with `queue = -1`, the packet will be enqueued into the RX drop-queue. If the drop-queue does not exist, the packet is dropped. The default value is `N=127`.

- `--disable-crc-strip`
Disable hardware CRC stripping.
- `--enable-lro`
Enable large receive offload.
- `--enable-rx-cksum`
Enable hardware RX checksum offload.
- `--enable-scatter`
Enable scatter (multi-segment) RX.
- `--disable-hw-vlan`
Disable hardware VLAN.
- `--disable-hw-vlan-filter`
Disable hardware VLAN filter.
- `--disable-hw-vlan-strip`
Disable hardware VLAN strip.
- `--disable-hw-vlan-extend`
Disable hardware VLAN extend.
- `--enable-drop-en`
Enable per-queue packet drop for packets with no descriptors.
- `--disable-rss`
Disable RSS (Receive Side Scaling).
- `--port-topology=mode`
Set port topology, where `mode` is `paired` (the default) or `chained`.
In `paired` mode, the forwarding is between pairs of ports, for example: (0,1), (2,3), (4,5).
In `chained` mode, the forwarding is to the next available port in the port mask, for example: (0,1), (1,2), (2,0).
The ordering of the ports can be changed using the `portlist testpmd` runtime function.
- `--forward-mode=mode`
Set the forwarding mode where `mode` is one of the following:
 - `io` (the default)
 - `mac`
 - `macswap`
 - `flowgen`
 - `rxonly`
 - `txonly`
 - `csum`
 - `icmpecho`
 - `ieee1588`

- `--rss-ip`
Set RSS functions for IPv4/IPv6 only.
- `--rss-udp`
Set RSS functions for IPv4/IPv6 and UDP.
- `--rxq=N`
Set the number of RX queues per port to N, where $1 \leq N \leq 65535$. The default value is 1.
- `--rxd=N`
Set the number of descriptors in the RX rings to N, where $N > 0$. The default value is 128.
- `--txq=N`
Set the number of TX queues per port to N, where $1 \leq N \leq 65535$. The default value is 1.
- `--txd=N`
Set the number of descriptors in the TX rings to N, where $N > 0$. The default value is 512.
- `--burst=N`
Set the number of packets per burst to N, where $1 \leq N \leq 512$. The default value is 16.
- `--mbcache=N`
Set the cache of mbuf memory pools to N, where $0 \leq N \leq 512$. The default value is 16.
- `--rxpt=N`
Set the prefetch threshold register of RX rings to N, where $N \geq 0$. The default value is 8.
- `--rxht=N`
Set the host threshold register of RX rings to N, where $N \geq 0$. The default value is 8.
- `--rxfreet=N`
Set the free threshold of RX descriptors to N, where $0 \leq N < \text{value of } -\text{rxd}$. The default value is 0.
- `--rxwt=N`
Set the write-back threshold register of RX rings to N, where $N \geq 0$. The default value is 4.
- `--txpt=N`
Set the prefetch threshold register of TX rings to N, where $N \geq 0$. The default value is 36.
- `--txht=N`
Set the host threshold register of TX rings to N, where $N \geq 0$. The default value is 0.

- `--txwt=N`
Set the write-back threshold register of TX rings to N, where $N \geq 0$. The default value is 0.
- `--txfreet=N`
Set the transmit free threshold of TX rings to N, where $0 \leq N \leq$ value of `--txd`. The default value is 0.
- `--txrst=N`
Set the transmit RS bit threshold of TX rings to N, where $0 \leq N \leq$ value of `--txd`. The default value is 0.
- `--txqflags=0XXXXXXXX`
Set the hexadecimal bitmask of TX queue flags, where $0 \leq N \leq 0x7FFFFFFF$. The default value is 0.

Note: When using hardware offload functions such as vlan or checksum add `txqflags=0` to force the full-featured TX code path. In some PMDs this may already be the default.

- `--rx-queue-stats-mapping=(port,queue,mapping) [, (port,queue,mapping)]`
Set the RX queues statistics counters mapping $0 \leq \text{mapping} \leq 15$.
- `--tx-queue-stats-mapping=(port,queue,mapping) [, (port,queue,mapping)]`
Set the TX queues statistics counters mapping $0 \leq \text{mapping} \leq 15$.
- `--no-flush-rx`
Don't flush the RX streams before starting forwarding. Used mainly with the PCAP PMD.
- `--txpkts=X[, Y]`
Set TX segment sizes or total packet length. Valid for `tx-only` and `flowgen` forwarding modes.
- `--disable-link-check`
Disable check on link status when starting/stopping ports.

TESTPMD RUNTIME FUNCTIONS

Where the `testpmd` application is started in interactive mode, (`-i|--interactive`), it displays a prompt that can be used to start and stop forwarding, configure the application, display statistics (including the extended NIC statistics aka `xstats`), set the Flow Director and other tasks:

```
testpmd>
```

The `testpmd` prompt has some, limited, readline support. Common bash command-line functions such as `Ctrl+a` and `Ctrl+e` to go to the start and end of the prompt line are supported as well as access to the command history via the up-arrow.

There is also support for tab completion. If you type a partial command and hit `<TAB>` you get a list of the available completions:

```
testpmd> show port <TAB>

info [Mul-choice STRING]: show|clear port info|stats|xstats|fdir|stat_qmap|dcb_tc X
info [Mul-choice STRING]: show|clear port info|stats|xstats|fdir|stat_qmap|dcb_tc all
stats [Mul-choice STRING]: show|clear port info|stats|xstats|fdir|stat_qmap|dcb_tc X
stats [Mul-choice STRING]: show|clear port info|stats|xstats|fdir|stat_qmap|dcb_tc all
...
```

Note: Some examples in this document are too long to fit on one line and are shown wrapped at “\” for display purposes:

```
testpmd> set flow_ctrl rx (on|off) tx (on|off) (high_water) (low_water) \
          (pause_time) (send_xon) (port_id)
```

In the real `testpmd>` prompt these commands should be on a single line.

4.1 Help Functions

The `testpmd` has on-line help for the functions that are available at runtime. These are divided into sections and can be accessed using `help`, `help section` or `help all`:

```
testpmd> help

help control      : Start and stop forwarding.
help display      : Displaying port, stats and config information.
help config       : Configuration information.
help ports        : Configuring ports.
help registers    : Reading and setting port registers.
help filters      : Filters configuration help.
help all          : All of the above sections.
```

4.2 Control Functions

4.2.1 start

Start packet forwarding with current configuration:

```
testpmd> start
```

4.2.2 start tx_first

Start packet forwarding with current configuration after sending specified number of bursts of packets:

```
testpmd> start tx_first ("burst_num")
```

The default burst number is 1 when `burst_num` not presented.

4.2.3 stop

Stop packet forwarding, and display accumulated statistics:

```
testpmd> stop
```

4.2.4 quit

Quit to prompt:

```
testpmd> quit
```

4.3 Display Functions

The functions in the following sections are used to display information about the testpmd configuration or the NIC status.

4.3.1 show port

Display information for a given port or all ports:

```
testpmd> show port (info|stats|xstats|fdir|stat_qmap|dcb_tc) (port_id|all)
```

The available information categories are:

- `info`: General port information such as MAC address.
- `stats`: RX/TX statistics.
- `xstats`: RX/TX extended NIC statistics.
- `fdir`: Flow Director information and statistics.
- `stat_qmap`: Queue statistics mapping.
- `dcb_tc`: DCB information such as TC mapping.

For example:


```
testpmd> show port info 0

***** Infos for port 0 *****

MAC address: XX:XX:XX:XX:XX:XX
Connect to socket: 0
memory allocation on the socket: 0
Link status: up
Link speed: 40000 Mbps
Link duplex: full-duplex
Promiscuous mode: enabled
Allmulticast mode: disabled
Maximum number of MAC addresses: 64
Maximum number of MAC addresses of hash filtering: 0
VLAN offload:
  strip on
  filter on
  qinq(extend) off
Redirection table size: 512
Supported flow types:
  ipv4-frag
  ipv4-tcp
  ipv4-udp
  ipv4-sctp
  ipv4-other
  ipv6-frag
  ipv6-tcp
  ipv6-udp
  ipv6-sctp
  ipv6-other
  l2_payload
  port
  vxlan
  geneve
  nvgre
```

4.3.2 show port rss reta

Display the rss redirection table entry indicated by masks on port X:

```
testpmd> show port (port_id) rss reta (size) (mask0, mask1...)
```

size is used to indicate the hardware supported reta size

4.3.3 show port rss-hash

Display the RSS hash functions and RSS hash key of a port:

```
testpmd> show port (port_id) rss-hash [key]
```

4.3.4 clear port

Clear the port statistics for a given port or for all ports:

```
testpmd> clear port (info|stats|xstats|fdir|stat_qmap) (port_id|all)
```

For example:

```
testpmd> clear port stats all
```

4.3.5 show (rxq|txq)

Display information for a given port's RX/TX queue:

```
testpmd> show (rxq|txq) info (port_id) (queue_id)
```

4.3.6 show config

Displays the configuration of the application. The configuration comes from the command-line, the runtime or the application defaults:

```
testpmd> show config (rxtx|cores|fwd|txpkts)
```

The available information categories are:

- `rxtx`: RX/TX configuration items.
- `cores`: List of forwarding cores.
- `fwd`: Packet forwarding configuration.
- `txpkts`: Packets to TX configuration.

For example:

```
testpmd> show config rxtx

io packet forwarding - CRC stripping disabled - packets/burst=16
nb forwarding cores=2 - nb forwarding ports=1
RX queues=1 - RX desc=128 - RX free threshold=0
RX threshold registers: pthresh=8 hthresh=8 wthresh=4
TX queues=1 - TX desc=512 - TX free threshold=0
TX threshold registers: pthresh=36 hthresh=0 wthresh=0
TX RS bit threshold=0 - TXQ flags=0x0
```

4.3.7 set fwd

Set the packet forwarding mode:

```
testpmd> set fwd (io|mac|macswap|flowgen| \
                rxonly|txonly|csum|icmpecho) (" "|retry)
```

`retry` can be specified for forwarding engines except `rx_only`.

The available information categories are:

- `io`: Forwards packets “as-is” in I/O mode. This is the fastest possible forwarding operation as it does not access packets data. This is the default mode.
- `mac`: Changes the source and the destination Ethernet addresses of packets before forwarding them. Default application behaviour is to set source Ethernet address to that of the transmitting interface, and destination address to a dummy value (set during init). The user may specify a target destination Ethernet address via the ‘eth-peer’ or ‘eth-peer-configfile’ command-line options. It is not currently possible to specify a specific source Ethernet address.
- `macswap`: MAC swap forwarding mode. Swaps the source and the destination Ethernet addresses of packets before forwarding them.

- `flowgen`: Multi-flow generation mode. Originates a number of flows (with varying destination IP addresses), and terminate receive traffic.
- `rxonly`: Receives packets but doesn't transmit them.
- `txonly`: Generates and transmits packets without receiving any.
- `csum`: Changes the checksum field with hardware or software methods depending on the offload flags on the packet.
- `icmpecho`: Receives a burst of packets, lookup for ICMP echo requests and, if any, send back ICMP echo replies.
- `ieee1588`: Demonstrate L2 IEEE1588 V2 PTP timestamping for RX and TX. Requires `CONFIG_RTE_LIBRTE_IEEE1588=y`.

Note: TX timestamping is only available in the "Full Featured" TX path. To force `testpmd` into this mode set `--txqflags=0`.

Example:

```
testpmd> set fwd rxonly

Set rxonly packet forwarding mode
```

4.3.8 read rxd

Display an RX descriptor for a port RX queue:

```
testpmd> read rxd (port_id) (queue_id) (rxd_id)
```

For example:

```
testpmd> read rxd 0 0 4
0x0000000B - 0x001D0180 / 0x0000000B - 0x001D0180
```

4.3.9 read txd

Display a TX descriptor for a port TX queue:

```
testpmd> read txd (port_id) (queue_id) (txd_id)
```

For example:

```
testpmd> read txd 0 0 4
0x00000001 - 0x24C3C440 / 0x000F0000 - 0x2330003C
```

4.4 Configuration Functions

The `testpmd` application can be configured from the runtime as well as from the command-line. This section details the available configuration functions that are available.

Note: Configuration changes only become active when forwarding is started/restarted.

4.4.1 set default

Reset forwarding to the default configuration:

```
testpmd> set default
```

4.4.2 set verbose

Set the debug verbosity level:

```
testpmd> set verbose (level)
```

Currently the only available levels are 0 (silent except for error) and 1 (fully verbose).

4.4.3 set nbport

Set the number of ports used by the application:

```
set nbport (num)
```

This is equivalent to the `--nb-ports` command-line option.

4.4.4 set nbcore

Set the number of cores used by the application:

```
testpmd> set nbcore (num)
```

This is equivalent to the `--nb-cores` command-line option.

Note: The number of cores used must not be greater than number of ports used multiplied by the number of queues per port.

4.4.5 set coremask

Set the forwarding cores hexadecimal mask:

```
testpmd> set coremask (mask)
```

This is equivalent to the `--coremask` command-line option.

Note: The master lcore is reserved for command line parsing only and cannot be masked on for packet forwarding.

4.4.6 set portmask

Set the forwarding ports hexadecimal mask:

```
testpmd> set portmask (mask)
```

This is equivalent to the `--portmask` command-line option.

4.4.7 set burst

Set number of packets per burst:

```
testpmd> set burst (num)
```

This is equivalent to the `--burst` command-line option.

When retry is enabled, the transmit delay time and number of retries can also be set:

```
testpmd> set burst tx delay (microseconds) retry (num)
```

4.4.8 set txpkts

Set the length of each segment of the TX-ONLY packets or length of packet for FLOWGEN mode:

```
testpmd> set txpkts (x[,y]*)
```

Where `x[,y]*` represents a CSV list of values, without white space.

4.4.9 set txsplit

Set the split policy for the TX packets, applicable for TX-ONLY and CSUM forwarding modes:

```
testpmd> set txsplit (off|on|rand)
```

Where:

- `off` disable packet copy & split for CSUM mode.
- `on` split outgoing packet into multiple segments. Size of each segment and number of segments per packet is determined by `set txpkts` command (see above).
- `rand` same as 'on', but number of segments per each packet is a random value between 1 and total number of segments.

4.4.10 set corelist

Set the list of forwarding cores:

```
testpmd> set corelist (x[,y]*)
```

For example, to change the forwarding cores:

```
testpmd> set corelist 3,1
testpmd> show config fwd
```

```
io packet forwarding - ports=2 - cores=2 - streams=2 - NUMA support disabled
Logical Core 3 (socket 0) forwards packets on 1 streams:
RX P=0/Q=0 (socket 0) -> TX P=1/Q=0 (socket 0) peer=02:00:00:00:00:01
Logical Core 1 (socket 0) forwards packets on 1 streams:
RX P=1/Q=0 (socket 0) -> TX P=0/Q=0 (socket 0) peer=02:00:00:00:00:00
```

Note: The cores are used in the same order as specified on the command line.

4.4.11 set portlist

Set the list of forwarding ports:

```
testpmd> set portlist (x[,y]*)
```

For example, to change the port forwarding:

```
testpmd> set portlist 0,2,1,3
testpmd> show config fwd
```

```
io packet forwarding - ports=4 - cores=1 - streams=4
Logical Core 3 (socket 0) forwards packets on 4 streams:
RX P=0/Q=0 (socket 0) -> TX P=2/Q=0 (socket 0) peer=02:00:00:00:00:01
RX P=2/Q=0 (socket 0) -> TX P=0/Q=0 (socket 0) peer=02:00:00:00:00:00
RX P=1/Q=0 (socket 0) -> TX P=3/Q=0 (socket 0) peer=02:00:00:00:00:03
RX P=3/Q=0 (socket 0) -> TX P=1/Q=0 (socket 0) peer=02:00:00:00:00:02
```

4.4.12 set tx loopback

Enable/disable tx loopback:

```
testpmd> set tx loopback (port_id) (on|off)
```

4.4.13 set drop enable

set drop enable bit for all queues:

```
testpmd> set all queues drop (port_id) (on|off)
```

4.4.14 set split drop enable (for VF)

set split drop enable bit for VF from PF:

```
testpmd> set vf split drop (port_id) (vf_id) (on|off)
```

4.4.15 set mac antispoof (for VF)

Set mac antispoof for a VF from the PF:

```
testpmd> set vf mac antispoof (port_id) (vf_id) (on|off)
```

4.4.16 vlan set strip

Set the VLAN strip on a port:

```
testpmd> vlan set strip (on|off) (port_id)
```

4.4.17 vlan set stripq

Set the VLAN strip for a queue on a port:

```
testpmd> vlan set stripq (on|off) (port_id,queue_id)
```

4.4.18 vlan set stripq (for VF)

Set VLAN strip for all queues in a pool for a VF from the PF:

```
testpmd> set vf vlan stripq (port_id) (vf_id) (on|off)
```

4.4.19 vlan set insert (for VF)

Set VLAN insert for a VF from the PF:

```
testpmd> set vf vlan insert (port_id) (vf_id) (vlan_id)
```

4.4.20 vlan set antispoof (for VF)

Set VLAN antispoof for a VF from the PF:

```
testpmd> set vf vlan antispoof (port_id) (vf_id) (on|off)
```

4.4.21 vlan set filter

Set the VLAN filter on a port:

```
testpmd> vlan set filter (on|off) (port_id)
```

4.4.22 vlan set qinq

Set the VLAN QinQ (extended queue in queue) on for a port:

```
testpmd> vlan set qinq (on|off) (port_id)
```

4.4.23 vlan set tpid

Set the inner or outer VLAN TPID for packet filtering on a port:

```
testpmd> vlan set (inner|outer) tpid (value) (port_id)
```

Note: TPID value must be a 16-bit number (value <= 65536).

4.4.24 rx_vlan add

Add a VLAN ID, or all identifiers, to the set of VLAN identifiers filtered by port ID:

```
testpmd> rx_vlan add (vlan_id|all) (port_id)
```

Note: VLAN filter must be set on that port. VLAN ID < 4096. Depending on the NIC used, number of vlan_ids may be limited to the maximum entries in VFTA table. This is important if enabling all vlan_ids.

4.4.25 rx_vlan rm

Remove a VLAN ID, or all identifiers, from the set of VLAN identifiers filtered by port ID:

```
testpmd> rx_vlan rm (vlan_id|all) (port_id)
```

4.4.26 rx_vlan add (for VF)

Add a VLAN ID, to the set of VLAN identifiers filtered for VF(s) for port ID:

```
testpmd> rx_vlan add (vlan_id) port (port_id) vf (vf_mask)
```

4.4.27 rx_vlan rm (for VF)

Remove a VLAN ID, from the set of VLAN identifiers filtered for VF(s) for port ID:

```
testpmd> rx_vlan rm (vlan_id) port (port_id) vf (vf_mask)
```

4.4.28 tunnel_filter add

Add a tunnel filter on a port:

```
testpmd> tunnel_filter add (port_id) (outer_mac) (inner_mac) (ip_addr) \
    (inner_vlan) (vxlan|nvgre|ipingre) (imac-ivlan|imac-ivlan-tenid|\
    imac-tenid|imac|omac-imac-tenid|oip|iip) (tenant_id) (queue_id)
```

The available information categories are:

- vxlan: Set tunnel type as VXLAN.
- nvgre: Set tunnel type as NVGRE.
- ipingre: Set tunnel type as IP-in-GRE.
- imac-ivlan: Set filter type as Inner MAC and VLAN.
- imac-ivlan-tenid: Set filter type as Inner MAC, VLAN and tenant ID.
- imac-tenid: Set filter type as Inner MAC and tenant ID.
- imac: Set filter type as Inner MAC.
- omac-imac-tenid: Set filter type as Outer MAC, Inner MAC and tenant ID.
- oip: Set filter type as Outer IP.
- iip: Set filter type as Inner IP.

Example:

```
testpmd> tunnel_filter add 0 68:05:CA:28:09:82 00:00:00:00:00:00 \
    192.168.2.2 0 ipingre oip 1 1
```

Set an IP-in-GRE tunnel on port 0, and the filter type is Outer IP.

4.4.29 tunnel_filter remove

Remove a tunnel filter on a port:

```
testpmd> tunnel_filter rm (port_id) (outer_mac) (inner_mac) (ip_addr) \  
    (inner_vlan) (vxlan|nvgre|ipingre) (imac-ivlan|imac-ivlan-tenid\  
    imac-tenid|imac|omac-imac-tenid|oip|iip) (tenant_id) (queue_id)
```

4.4.30 rx_vxlan_port add

Add an UDP port for VXLAN packet filter on a port:

```
testpmd> rx_vxlan_port add (udp_port) (port_id)
```

4.4.31 rx_vxlan_port remove

Remove an UDP port for VXLAN packet filter on a port:

```
testpmd> rx_vxlan_port rm (udp_port) (port_id)
```

4.4.32 tx_vlan set

Set hardware insertion of VLAN IDs in packets sent on a port:

```
testpmd> tx_vlan set (port_id) vlan_id[, vlan_id_outer]
```

For example, set a single VLAN ID (5) insertion on port 0:

```
tx_vlan set 0 5
```

Or, set double VLAN ID (inner: 2, outer: 3) insertion on port 1:

```
tx_vlan set 1 2 3
```

4.4.33 tx_vlan set pvid

Set port based hardware insertion of VLAN ID in packets sent on a port:

```
testpmd> tx_vlan set pvid (port_id) (vlan_id) (on|off)
```

4.4.34 tx_vlan reset

Disable hardware insertion of a VLAN header in packets sent on a port:

```
testpmd> tx_vlan reset (port_id)
```

4.4.35 csum set

Select hardware or software calculation of the checksum when transmitting a packet using the csum forwarding engine:

```
testpmd> csum set (ip|udp|tcp|sctp|outer-ip) (hw|sw) (port_id)
```

Where:

- ip|udp|tcp|sctp always relate to the inner layer.

- `outer-ip` relates to the outer IP layer (only for IPv4) in the case where the packet is recognized as a tunnel packet by the forwarding engine (vxlan, gre and ipip are supported). See also the `csum parse-tunnel` command.

Note: Check the NIC Datasheet for hardware limits.

4.4.36 `csum parse-tunnel`

Define how tunneled packets should be handled by the `csum` forward engine:

```
testpmd> csum parse-tunnel (on|off) (tx_port_id)
```

If enabled, the `csum` forward engine will try to recognize supported tunnel headers (vxlan, gre, ipip).

If disabled, treat tunnel packets as non-tunneled packets (a inner header is handled as a packet payload).

Note: The port argument is the TX port like in the `csum set` command.

Example:

Consider a packet in packet like the following:

```
eth_out/ipv4_out/udp_out/vxlan/eth_in/ipv4_in/tcp_in
```

- If `parse-tunnel` is enabled, the `ip|udp|tcp|sctp` parameters of `csum set` command relate to the inner headers (here `ipv4_in` and `tcp_in`), and the `outer-ip` parameter relates to the outer headers (here `ipv4_out`).
- If `parse-tunnel` is disabled, the `ip|udp|tcp|sctp` parameters of `csum set` command relate to the outer headers, here `ipv4_out` and `udp_out`.

4.4.37 `csum show`

Display tx checksum offload configuration:

```
testpmd> csum show (port_id)
```

4.4.38 `tso set`

Enable TCP Segmentation Offload (TSO) in the `csum` forwarding engine:

```
testpmd> tso set (segsz) (port_id)
```

Note: Check the NIC datasheet for hardware limits.

4.4.39 tso show

Display the status of TCP Segmentation Offload:

```
testpmd> tso show (port_id)
```

4.4.40 mac_addr add

Add an alternative MAC address to a port:

```
testpmd> mac_addr add (port_id) (XX:XX:XX:XX:XX:XX)
```

4.4.41 mac_addr remove

Remove a MAC address from a port:

```
testpmd> mac_addr remove (port_id) (XX:XX:XX:XX:XX:XX)
```

4.4.42 mac_addr add (for VF)

Add an alternative MAC address for a VF to a port:

```
testpmd> mac_add add port (port_id) vf (vf_id) (XX:XX:XX:XX:XX:XX)
```

4.4.43 mac_addr set (for VF)

Set the MAC address for a VF from the PF:

```
testpmd> set vf mac addr (port_id) (vf_id) (XX:XX:XX:XX:XX:XX)
```

4.4.44 set port-uta

Set the unicast hash filter(s) on/off for a port:

```
testpmd> set port (port_id) uta (XX:XX:XX:XX:XX:XX|all) (on|off)
```

4.4.45 set promisc

Set the promiscuous mode on for a port or for all ports. In promiscuous mode packets are not dropped if they aren't for the specified MAC address:

```
testpmd> set promisc (port_id|all) (on|off)
```

4.4.46 set allmulti

Set the allmulti mode for a port or for all ports:

```
testpmd> set allmulti (port_id|all) (on|off)
```

Same as the ifconfig (8) option. Controls how multicast packets are handled.

4.4.47 set flow_ctrl rx

Set the link flow control parameter on a port:

```
testpmd> set flow_ctrl rx (on|off) tx (on|off) (high_water) (low_water) \  
          (pause_time) (send_xon) mac_ctrl_frame_fwd (on|off) \  
          autoneg (on|off) (port_id)
```

Where:

- `high_water` (integer): High threshold value to trigger XOFF.
- `low_water` (integer): Low threshold value to trigger XON.
- `pause_time` (integer): Pause quota in the Pause frame.
- `send_xon` (0/1): Send XON frame.
- `mac_ctrl_frame_fwd`: Enable receiving MAC control frames.
- `autoneg`: Change the auto-negotiation parameter.

4.4.48 set pfc_ctrl rx

Set the priority flow control parameter on a port:

```
testpmd> set pfc_ctrl rx (on|off) tx (on|off) (high_water) (low_water) \  
          (pause_time) (priority) (port_id)
```

Where:

- `high_water` (integer): High threshold value.
- `low_water` (integer): Low threshold value.
- `pause_time` (integer): Pause quota in the Pause frame.
- `priority` (0-7): VLAN User Priority.

4.4.49 set stat_qmap

Set statistics mapping (qmapping 0..15) for RX/TX queue on port:

```
testpmd> set stat_qmap (tx|rx) (port_id) (queue_id) (qmapping)
```

For example, to set rx queue 2 on port 0 to mapping 5:

```
testpmd>set stat_qmap rx 0 2 5
```

4.4.50 set port - rx/tx (for VF)

Set VF receive/transmit from a port:

```
testpmd> set port (port_id) vf (vf_id) (rx|tx) (on|off)
```

4.4.51 set port - mac address filter (for VF)

Add/Remove unicast or multicast MAC addr filter for a VF:

```
testpmd> set port (port_id) vf (vf_id) (mac_addr) \
    (exact-mac|exact-mac-vlan|hashmac|hashmac-vlan) (on|off)
```

4.4.52 set port - rx mode(for VF)

Set the VF receive mode of a port:

```
testpmd> set port (port_id) vf (vf_id) \
    rxmode (AUPE|ROPE|BAM|MPE) (on|off)
```

The available receive modes are:

- AUPE: Accepts untagged VLAN.
- ROPE: Accepts unicast hash.
- BAM: Accepts broadcast packets.
- MPE: Accepts all multicast packets.

4.4.53 set port - tx_rate (for Queue)

Set TX rate limitation for a queue on a port:

```
testpmd> set port (port_id) queue (queue_id) rate (rate_value)
```

4.4.54 set port - tx_rate (for VF)

Set TX rate limitation for queues in VF on a port:

```
testpmd> set port (port_id) vf (vf_id) rate (rate_value) queue_mask (queue_mask)
```

4.4.55 set port - mirror rule

Set pool or vlan type mirror rule for a port:

```
testpmd> set port (port_id) mirror-rule (rule_id) \
    (pool-mirror-up|pool-mirror-down|vlan-mirror) \
    (poolmask|vlanid[,vlanid]*) dst-pool (pool_id) (on|off)
```

Set link mirror rule for a port:

```
testpmd> set port (port_id) mirror-rule (rule_id) \
    (uplink-mirror|downlink-mirror) dst-pool (pool_id) (on|off)
```

For example to enable mirror traffic with vlan 0,1 to pool 0:

```
set port 0 mirror-rule 0 vlan-mirror 0,1 dst-pool 0 on
```

4.4.56 reset port - mirror rule

Reset a mirror rule for a port:

```
testpmd> reset port (port_id) mirror-rule (rule_id)
```

4.4.57 set flush_rx

Set the flush on RX streams before forwarding. The default is flush on. Mainly used with PCAP drivers to turn off the default behavior of flushing the first 512 packets on RX streams:

```
testpmd> set flush_rx off
```

4.4.58 set bypass mode

Set the bypass mode for the lowest port on bypass enabled NIC:

```
testpmd> set bypass mode (normal|bypass|isolate) (port_id)
```

4.4.59 set bypass event

Set the event required to initiate specified bypass mode for the lowest port on a bypass enabled:

```
testpmd> set bypass event (timeout|os_on|os_off|power_on|power_off) \
mode (normal|bypass|isolate) (port_id)
```

Where:

- `timeout`: Enable bypass after watchdog timeout.
- `os_on`: Enable bypass when OS/board is powered on.
- `os_off`: Enable bypass when OS/board is powered off.
- `power_on`: Enable bypass when power supply is turned on.
- `power_off`: Enable bypass when power supply is turned off.

4.4.60 set bypass timeout

Set the bypass watchdog timeout to `n` seconds where 0 = instant:

```
testpmd> set bypass timeout (0|1.5|2|3|4|8|16|32)
```

4.4.61 show bypass config

Show the bypass configuration for a bypass enabled NIC using the lowest port on the NIC:

```
testpmd> show bypass config (port_id)
```

4.4.62 set link up

Set link up for a port:

```
testpmd> set link-up port (port id)
```

4.4.63 set link down

Set link down for a port:

```
testpmd> set link-down port (port id)
```

4.4.64 E-tag set

Enable E-tag insertion for a VF on a port:

```
testpmd> E-tag set insertion on port-tag-id (value) port (port_id) vf (vf_id)
```

Disable E-tag insertion for a VF on a port:

```
testpmd> E-tag set insertion off port (port_id) vf (vf_id)
```

Enable/disable E-tag stripping on a port:

```
testpmd> E-tag set stripping (on|off) port (port_id)
```

Enable/disable E-tag based forwarding on a port:

```
testpmd> E-tag set forwarding (on|off) port (port_id)
```

Add an E-tag forwarding filter on a port:

```
testpmd> E-tag set filter add e-tag-id (value) dst-pool (pool_id) port (port_id)
```

Delete an E-tag forwarding filter on a port:: testpmd> E-tag set filter del e-tag-id (value)
port (port_id)

4.5 Port Functions

The following sections show functions for configuring ports.

Note: Port configuration changes only become active when forwarding is started/restarted.

4.5.1 port attach

Attach a port specified by pci address or virtual device args:

```
testpmd> port attach (identifier)
```

To attach a new pci device, the device should be recognized by kernel first. Then it should be moved under DPDK management. Finally the port can be attached to testpmd.

For example, to move a pci device using ixgbe under DPDK management:

```
# Check the status of the available devices.
./tools/dpdk-devbind.py --status

Network devices using DPDK-compatible driver
=====
<none>

Network devices using kernel driver
=====
0000:0a:00.0 '82599ES 10-Gigabit' if=eth2 drv=ixgbe unused=
```

```
# Bind the device to igb_uio.
sudo ./tools/dpdk-devbind.py -b igb_uio 0000:0a:00.0
```

```
# Recheck the status of the devices.
./tools/dpdk-devbind.py --status
Network devices using DPDK-compatible driver
=====
0000:0a:00.0 '82599ES 10-Gigabit' drv=igb_uio unused=
```

To attach a port created by virtual device, above steps are not needed.

For example, to attach a port whose pci address is 0000:0a:00.0.

```
testpmd> port attach 0000:0a:00.0
Attaching a new port...
EAL: PCI device 0000:0a:00.0 on NUMA socket -1
EAL: probe driver: 8086:10fb rte_ixgbe_pmd
EAL: PCI memory mapped at 0x7f83bfa00000
EAL: PCI memory mapped at 0x7f83bfa80000
PMD: eth_ixgbe_dev_init(): MAC: 2, PHY: 18, SFP+: 5
PMD: eth_ixgbe_dev_init(): port 0 vendorID=0x8086 deviceID=0x10fb
Port 0 is attached. Now total ports is 1
Done
```

For example, to attach a port created by pcap PMD.

```
testpmd> port attach net_pcap0
Attaching a new port...
PMD: Initializing pmd_pcap for net_pcap0
PMD: Creating pcap-backed ethdev on numa socket 0
Port 0 is attached. Now total ports is 1
Done
```

In this case, identifier is net_pcap0. This identifier format is the same as --vdev format of DPDK applications.

For example, to re-attach a bonded port which has been previously detached, the mode and slave parameters must be given.

```
testpmd> port attach net_bond_0,mode=0,slave=1
Attaching a new port...
EAL: Initializing pmd_bond for net_bond_0
EAL: Create bonded device net_bond_0 on port 0 in mode 0 on socket 0.
Port 0 is attached. Now total ports is 1
Done
```

4.5.2 port detach

Detach a specific port:

```
testpmd> port detach (port_id)
```

Before detaching a port, the port should be stopped and closed.

For example, to detach a pci device port 0.

```
testpmd> port stop 0
Stopping ports...
Done
testpmd> port close 0
Closing ports...
```



```

Done

testpmd> port detach 0
Detaching a port...
EAL: PCI device 0000:0a:00.0 on NUMA socket -1
EAL:   remove driver: 8086:10fb rte_ixgbe_pmd
EAL:   PCI memory unmapped at 0x7f83bfa00000
EAL:   PCI memory unmapped at 0x7f83bfa80000
Done

```

For example, to detach a virtual device port 0.

```

testpmd> port stop 0
Stopping ports...
Done
testpmd> port close 0
Closing ports...
Done

testpmd> port detach 0
Detaching a port...
PMD: Closing pcap ethdev on numa socket 0
Port 'net_pcap0' is detached. Now total ports is 0
Done

```

To remove a pci device completely from the system, first detach the port from testpmd. Then the device should be moved under kernel management. Finally the device can be removed using kernel pci hotplug functionality.

For example, to move a pci device under kernel management:

```

sudo ./tools/dpdk-devbind.py -b ixgbe 0000:0a:00.0

./tools/dpdk-devbind.py --status

Network devices using DPDK-compatible driver
=====
<none>

Network devices using kernel driver
=====
0000:0a:00.0 '82599ES 10-Gigabit' if=eth2 drv=ixgbe unused=igb_uio

```

To remove a port created by a virtual device, above steps are not needed.

4.5.3 port start

Start all ports or a specific port:

```
testpmd> port start (port_id|all)
```

4.5.4 port stop

Stop all ports or a specific port:

```
testpmd> port stop (port_id|all)
```

4.5.5 port close

Close all ports or a specific port:

```
testpmd> port close (port_id|all)
```

4.5.6 port start/stop queue

Start/stop a rx/tx queue on a specific port:

```
testpmd> port (port_id) (rxq|txq) (queue_id) (start|stop)
```

Only take effect when port is started.

4.5.7 port config - speed

Set the speed and duplex mode for all ports or a specific port:

```
testpmd> port config (port_id|all) speed (10|100|1000|10000|25000|40000|50000|100000|auto) \
duplex (half|full|auto)
```

4.5.8 port config - queues/descriptors

Set number of queues/descriptors for rxq, txq, rxd and txd:

```
testpmd> port config all (rxq|txq|rxd|txd) (value)
```

This is equivalent to the `--rxq`, `--txq`, `--rxd` and `--txd` command-line options.

4.5.9 port config - max-pkt-len

Set the maximum packet length:

```
testpmd> port config all max-pkt-len (value)
```

This is equivalent to the `--max-pkt-len` command-line option.

4.5.10 port config - CRC Strip

Set hardware CRC stripping on or off for all ports:

```
testpmd> port config all crc-strip (on|off)
```

CRC stripping is on by default.

The `off` option is equivalent to the `--disable-crc-strip` command-line option.

4.5.11 port config - scatter

Set RX scatter mode on or off for all ports:

```
testpmd> port config all scatter (on|off)
```

RX scatter mode is off by default.

The `on` option is equivalent to the `--enable-scatter` command-line option.

4.5.12 port config - TX queue flags

Set a hexadecimal bitmap of TX queue flags for all ports:

```
testpmd> port config all txqflags value
```

This command is equivalent to the `--txqflags` command-line option.

4.5.13 port config - RX Checksum

Set hardware RX checksum offload to on or off for all ports:

```
testpmd> port config all rx-cksum (on|off)
```

Checksum offload is off by default.

The `on` option is equivalent to the `--enable-rx-cksum` command-line option.

4.5.14 port config - VLAN

Set hardware VLAN on or off for all ports:

```
testpmd> port config all hw-vlan (on|off)
```

Hardware VLAN is on by default.

The `off` option is equivalent to the `--disable-hw-vlan` command-line option.

4.5.15 port config - VLAN filter

Set hardware VLAN filter on or off for all ports:

```
testpmd> port config all hw-vlan-filter (on|off)
```

Hardware VLAN filter is on by default.

The `off` option is equivalent to the `--disable-hw-vlan-filter` command-line option.

4.5.16 port config - VLAN strip

Set hardware VLAN strip on or off for all ports:

```
testpmd> port config all hw-vlan-strip (on|off)
```

Hardware VLAN strip is on by default.

The `off` option is equivalent to the `--disable-hw-vlan-strip` command-line option.

4.5.17 port config - VLAN extend

Set hardware VLAN extend on or off for all ports:

```
testpmd> port config all hw-vlan-extend (on|off)
```

Hardware VLAN extend is off by default.

The `off` option is equivalent to the `--disable-hw-vlan-extend` command-line option.

4.5.18 port config - Drop Packets

Set packet drop for packets with no descriptors on or off for all ports:

```
testpmd> port config all drop-en (on|off)
```

Packet dropping for packets with no descriptors is off by default.

The `on` option is equivalent to the `--enable-drop-en` command-line option.

4.5.19 port config - RSS

Set the RSS (Receive Side Scaling) mode on or off:

```
testpmd> port config all rss (all|ip|tcp|udp|sctp|ether|port|vxlan|geneve|nvgre|none)
```

RSS is on by default.

The `none` option is equivalent to the `--disable-rss` command-line option.

4.5.20 port config - RSS Reta

Set the RSS (Receive Side Scaling) redirection table:

```
testpmd> port config all rss reta (hash,queue) [, (hash,queue)]
```

4.5.21 port config - DCB

Set the DCB mode for an individual port:

```
testpmd> port config (port_id) dcb vt (on|off) (traffic_class) pfc (on|off)
```

The traffic class should be 4 or 8.

4.5.22 port config - Burst

Set the number of packets per burst:

```
testpmd> port config all burst (value)
```

This is equivalent to the `--burst` command-line option.

4.5.23 port config - Threshold

Set thresholds for TX/RX queues:

```
testpmd> port config all (threshold) (value)
```

Where the threshold type can be:

- `txpt`: Set the prefetch threshold register of the TX rings, $0 \leq \text{value} \leq 255$.
- `txht`: Set the host threshold register of the TX rings, $0 \leq \text{value} \leq 255$.
- `txwt`: Set the write-back threshold register of the TX rings, $0 \leq \text{value} \leq 255$.
- `rxpt`: Set the prefetch threshold register of the RX rings, $0 \leq \text{value} \leq 255$.

- `rxht`: Set the host threshold register of the RX rings, $0 \leq \text{value} \leq 255$.
- `rxwt`: Set the write-back threshold register of the RX rings, $0 \leq \text{value} \leq 255$.
- `txfreet`: Set the transmit free threshold of the TX rings, $0 \leq \text{value} \leq \text{txd}$.
- `rxfreet`: Set the transmit free threshold of the RX rings, $0 \leq \text{value} \leq \text{rxd}$.
- `txrst`: Set the transmit RS bit threshold of TX rings, $0 \leq \text{value} \leq \text{txd}$.

These threshold options are also available from the command-line.

4.5.24 port config - E-tag

Set the value of ether-type for E-tag:

```
testpmd> port config (port_id|all) l2-tunnel E-tag ether-type (value)
```

Enable/disable the E-tag support:

```
testpmd> port config (port_id|all) l2-tunnel E-tag (enable|disable)
```

4.6 Link Bonding Functions

The Link Bonding functions make it possible to dynamically create and manage link bonding devices from within testpmd interactive prompt.

4.6.1 create bonded device

Create a new bonding device:

```
testpmd> create bonded device (mode) (socket)
```

For example, to create a bonded device in mode 1 on socket 0:

```
testpmd> create bonded device 1 0
created new bonded device (port X)
```

4.6.2 add bonding slave

Adds Ethernet device to a Link Bonding device:

```
testpmd> add bonding slave (slave id) (port id)
```

For example, to add Ethernet device (port 6) to a Link Bonding device (port 10):

```
testpmd> add bonding slave 6 10
```

4.6.3 remove bonding slave

Removes an Ethernet slave device from a Link Bonding device:

```
testpmd> remove bonding slave (slave id) (port id)
```

For example, to remove Ethernet slave device (port 6) to a Link Bonding device (port 10):

```
testpmd> remove bonding slave 6 10
```

4.6.4 set bonding mode

Set the Link Bonding mode of a Link Bonding device:

```
testpmd> set bonding mode (value) (port id)
```

For example, to set the bonding mode of a Link Bonding device (port 10) to broadcast (mode 3):

```
testpmd> set bonding mode 3 10
```

4.6.5 set bonding primary

Set an Ethernet slave device as the primary device on a Link Bonding device:

```
testpmd> set bonding primary (slave id) (port id)
```

For example, to set the Ethernet slave device (port 6) as the primary port of a Link Bonding device (port 10):

```
testpmd> set bonding primary 6 10
```

4.6.6 set bonding mac

Set the MAC address of a Link Bonding device:

```
testpmd> set bonding mac (port id) (mac)
```

For example, to set the MAC address of a Link Bonding device (port 10) to 00:00:00:00:00:01:

```
testpmd> set bonding mac 10 00:00:00:00:00:01
```

4.6.7 set bonding xmit_balance_policy

Set the transmission policy for a Link Bonding device when it is in Balance XOR mode:

```
testpmd> set bonding xmit_balance_policy (port_id) (l2|l23|l34)
```

For example, set a Link Bonding device (port 10) to use a balance policy of layer 3+4 (IP addresses & UDP ports):

```
testpmd> set bonding xmit_balance_policy 10 l34
```

4.6.8 set bonding mon_period

Set the link status monitoring polling period in milliseconds for a bonding device.

This adds support for PMD slave devices which do not support link status interrupts. When the `mon_period` is set to a value greater than 0 then all PMD's which do not support link status ISR will be queried every polling interval to check if their link status has changed:

```
testpmd> set bonding mon_period (port_id) (value)
```

For example, to set the link status monitoring polling period of bonded device (port 5) to 150ms:

```
testpmd> set bonding mon_period 5 150
```

4.6.9 show bonding config

Show the current configuration of a Link Bonding device:

```
testpmd> show bonding config (port id)
```

For example, to show the configuration a Link Bonding device (port 9) with 3 slave devices (1, 3, 4) in balance mode with a transmission policy of layer 2+3:

```
testpmd> show bonding config 9
Bonding mode: 2
Balance Xmit Policy: BALANCE_XMIT_POLICY_LAYER23
Slaves (3): [1 3 4]
Active Slaves (3): [1 3 4]
Primary: [3]
```

4.7 Register Functions

The Register Functions can be used to read from and write to registers on the network card referenced by a port number. This is mainly useful for debugging purposes. Reference should be made to the appropriate datasheet for the network card for details on the register addresses and fields that can be accessed.

4.7.1 read reg

Display the value of a port register:

```
testpmd> read reg (port_id) (address)
```

For example, to examine the Flow Director control register (FDIRCTL, 0x0000EE00) on an Intel 82599 10 GbE Controller:

```
testpmd> read reg 0 0xEE00
port 0 PCI register at offset 0xEE00: 0x4A060029 (1241907241)
```

4.7.2 read regfield

Display a port register bit field:

```
testpmd> read regfield (port_id) (address) (bit_x) (bit_y)
```

For example, reading the lowest two bits from the register in the example above:

```
testpmd> read regfield 0 0xEE00 0 1
port 0 PCI register at offset 0xEE00: bits[0, 1]=0x1 (1)
```

4.7.3 read regbit

Display a single port register bit:

```
testpmd> read regbit (port_id) (address) (bit_x)
```

For example, reading the lowest bit from the register in the example above:

```
testpmd> read regbit 0 0xEE00 0
port 0 PCI register at offset 0xEE00: bit 0=1
```

4.7.4 write reg

Set the value of a port register:

```
testpmd> write reg (port_id) (address) (value)
```

For example, to clear a register:

```
testpmd> write reg 0 0xEE00 0x0
port 0 PCI register at offset 0xEE00: 0x00000000 (0)
```

4.7.5 write regfield

Set bit field of a port register:

```
testpmd> write regfield (port_id) (address) (bit_x) (bit_y) (value)
```

For example, writing to the register cleared in the example above:

```
testpmd> write regfield 0 0xEE00 0 1 2
port 0 PCI register at offset 0xEE00: 0x00000002 (2)
```

4.7.6 write regbit

Set single bit value of a port register:

```
testpmd> write regbit (port_id) (address) (bit_x) (value)
```

For example, to set the high bit in the register from the example above:

```
testpmd> write regbit 0 0xEE00 31 1
port 0 PCI register at offset 0xEE00: 0x8000000A (2147483658)
```

4.8 Filter Functions

This section details the available filter functions that are available.

4.8.1 ethertype_filter

Add or delete a L2 Ethertype filter, which identify packets by their L2 Ethertype mainly assign them to a receive queue:

```
ethertype_filter (port_id) (add|del) (mac_addr|mac_ignr) (mac_address) \
                ethertype (ether_type) (drop|fwd) queue (queue_id)
```

The available information parameters are:

- `port_id`: The port which the Ethertype filter assigned on.
- `mac_addr`: Compare destination mac address.
- `mac_ignr`: Ignore destination mac address match.
- `mac_address`: Destination mac address to match.
- `ether_type`: The EtherType value want to match, for example 0x0806 for ARP packet. 0x0800 (IPv4) and 0x86DD (IPv6) are invalid.

- `queue_id`: The receive queue associated with this EtherType filter. It is meaningless when deleting or dropping.

Example, to add/remove an ethertype filter rule:

```
testpmd> ethertype_filter 0 add mac_ignr 00:11:22:33:44:55 \  
ethertype 0x0806 fwd queue 3  
  
testpmd> ethertype_filter 0 del mac_ignr 00:11:22:33:44:55 \  
ethertype 0x0806 fwd queue 3
```

4.8.2 2tuple_filter

Add or delete a 2-tuple filter, which identifies packets by specific protocol and destination TCP/UDP port and forwards packets into one of the receive queues:

```
2tuple_filter (port_id) (add|del) dst_port (dst_port_value) \  
protocol (protocol_value) mask (mask_value) \  
tcp_flags (tcp_flags_value) priority (prio_value) \  
queue (queue_id)
```

The available information parameters are:

- `port_id`: The port which the 2-tuple filter assigned on.
- `dst_port_value`: Destination port in L4.
- `protocol_value`: IP L4 protocol.
- `mask_value`: Participates in the match or not by bit for field above, 1b means participate.
- `tcp_flags_value`: TCP control bits. The non-zero value is invalid, when the `pro_value` is not set to 0x06 (TCP).
- `prio_value`: Priority of this filter.
- `queue_id`: The receive queue associated with this 2-tuple filter.

Example, to add/remove an 2tuple filter rule:

```
testpmd> 2tuple_filter 0 add dst_port 32 protocol 0x06 mask 0x03 \  
tcp_flags 0x02 priority 3 queue 3  
  
testpmd> 2tuple_filter 0 del dst_port 32 protocol 0x06 mask 0x03 \  
tcp_flags 0x02 priority 3 queue 3
```

4.8.3 5tuple_filter

Add or delete a 5-tuple filter, which consists of a 5-tuple (protocol, source and destination IP addresses, source and destination TCP/UDP/SCTP port) and routes packets into one of the receive queues:

```
5tuple_filter (port_id) (add|del) dst_ip (dst_address) src_ip \  
(src_address) dst_port (dst_port_value) \  
src_port (src_port_value) protocol (protocol_value) \  
mask (mask_value) tcp_flags (tcp_flags_value) \  
priority (prio_value) queue (queue_id)
```

The available information parameters are:

- `port_id`: The port which the 5-tuple filter assigned on.

- `dst_address`: Destination IP address.
- `src_address`: Source IP address.
- `dst_port_value`: TCP/UDP destination port.
- `src_port_value`: TCP/UDP source port.
- `protocol_value`: L4 protocol.
- `mask_value`: Participates in the match or not by bit for field above, 1b means participate
- `tcp_flags_value`: TCP control bits. The non-zero value is invalid, when the `protocol_value` is not set to 0x06 (TCP).
- `prio_value`: The priority of this filter.
- `queue_id`: The receive queue associated with this 5-tuple filter.

Example, to add/remove an 5tuple filter rule:

```
testpmd> 5tuple_filter 0 add dst_ip 2.2.2.5 src_ip 2.2.2.4 \
dst_port 64 src_port 32 protocol 0x06 mask 0x1F \
flags 0x0 priority 3 queue 3

testpmd> 5tuple_filter 0 del dst_ip 2.2.2.5 src_ip 2.2.2.4 \
dst_port 64 src_port 32 protocol 0x06 mask 0x1F \
flags 0x0 priority 3 queue 3
```

4.8.4 syn_filter

Using the SYN filter, TCP packets whose *SYN* flag is set can be forwarded to a separate queue:

```
syn_filter (port_id) (add|del) priority (high|low) queue (queue_id)
```

The available information parameters are:

- `port_id`: The port which the SYN filter assigned on.
- `high`: This SYN filter has higher priority than other filters.
- `low`: This SYN filter has lower priority than other filters.
- `queue_id`: The receive queue associated with this SYN filter

Example:

```
testpmd> syn_filter 0 add priority high queue 3
```

4.8.5 flex_filter

With flex filter, packets can be recognized by any arbitrary pattern within the first 128 bytes of the packet and routed into one of the receive queues:

```
flex_filter (port_id) (add|del) len (len_value) bytes (bytes_value) \
mask (mask_value) priority (prio_value) queue (queue_id)
```

The available information parameters are:

- `port_id`: The port which the Flex filter is assigned on.
- `len_value`: Filter length in bytes, no greater than 128.


```

dst (dst_ip_address) (dst_port) \
tos (tos_value) ttl (ttl_value) \
vlan (vlan_value) flexbytes (flexbytes_value) \
(drop|fwd) queue pf|vf(vf_id) (queue_id) \
fd_id (fd_id_value)

flow_director_filter (port_id) mode IP (add|del|update) \
flow (ipv4-sctp|ipv6-sctp) \
src (src_ip_address) (src_port) \
dst (dst_ip_address) (dst_port) \
tos (tos_value) ttl (ttl_value) \
tag (verification_tag) vlan (vlan_value) \
flexbytes (flexbytes_value) (drop|fwd) \
pf|vf(vf_id) queue (queue_id) fd_id (fd_id_value)

flow_director_filter (port_id) mode IP (add|del|update) flow l2_payload \
ether (ethertype) flexbytes (flexbytes_value) \
(drop|fwd) pf|vf(vf_id) queue (queue_id) \
fd_id (fd_id_value)

flow_director_filter (port_id) mode MAC-VLAN (add|del|update) \
mac (mac_address) vlan (vlan_value) \
flexbytes (flexbytes_value) (drop|fwd) \
queue (queue_id) fd_id (fd_id_value)

flow_director_filter (port_id) mode Tunnel (add|del|update) \
mac (mac_address) vlan (vlan_value) \
tunnel (NVGRE|VxLAN) tunnel-id (tunnel_id_value) \
flexbytes (flexbytes_value) (drop|fwd) \
queue (queue_id) fd_id (fd_id_value)

```

For example, to add an ipv4-udp flow type filter:

```

testpmd> flow_director_filter 0 mode IP add flow ipv4-udp src 2.2.2.3 32 \
dst 2.2.2.5 33 tos 2 ttl 40 vlan 0x1 flexbytes (0x88,0x48) \
fwd pf queue 1 fd_id 1

```

For example, add an ipv4-other flow type filter:

```

testpmd> flow_director_filter 0 mode IP add flow ipv4-other src 2.2.2.3 \
dst 2.2.2.5 tos 2 proto 20 ttl 40 vlan 0x1 \
flexbytes (0x88,0x48) fwd pf queue 1 fd_id 1

```

4.8.7 flush_flow_director

Flush all flow director filters on a device:

```

testpmd> flush_flow_director (port_id)

```

Example, to flush all flow director filter on port 0:

```

testpmd> flush_flow_director 0

```

4.8.8 flow_director_mask

Set flow director's input masks:

```

flow_director_mask (port_id) mode IP vlan (vlan_value) \
src_mask (ipv4_src) (ipv6_src) (src_port) \
dst_mask (ipv4_dst) (ipv6_dst) (dst_port)

flow_director_mask (port_id) mode MAC-VLAN vlan (vlan_value)

```

```
flow_director_mask (port_id) mode Tunnel vlan (vlan_value) \
    mac (mac_value) tunnel-type (tunnel_type_value) \
    tunnel-id (tunnel_id_value)
```

Example, to set flow director mask on port 0:

```
testpmd> flow_director_mask 0 mode IP vlan 0xefff \
    src_mask 255.255.255.255 \
    FFFF:FFFF:FFFF:FFFF:FFFF:FFFF:FFFF:FFFF 0xFFFF \
    dst_mask 255.255.255.255 \
    FFFF:FFFF:FFFF:FFFF:FFFF:FFFF:FFFF:FFFF 0xFFFF
```

4.8.9 flow_director_flex_mask

set masks of flow director's flexible payload based on certain flow type:

```
testpmd> flow_director_flex_mask (port_id) \
    flow (none|ipv4-other|ipv4-frag|ipv4-tcp|ipv4-udp|ipv4-sctp| \
    ipv6-other|ipv6-frag|ipv6-tcp|ipv6-udp|ipv6-sctp| \
    l2_payload|all) (mask)
```

Example, to set flow director's flex mask for all flow type on port 0:

```
testpmd> flow_director_flex_mask 0 flow all \
    (0xff,0xff,0,0,0,0,0,0,0,0,0,0,0,0,0,0)
```

4.8.10 flow_director_flex_payload

Configure flexible payload selection:

```
flow_director_flex_payload (port_id) (raw|l2|l3|l4) (config)
```

For example, to select the first 16 bytes from the offset 4 (bytes) of packet's payload as flexible payload:

```
testpmd> flow_director_flex_payload 0 14 \
    (4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19)
```

4.8.11 get_sym_hash_ena_per_port

Get symmetric hash enable configuration per port:

```
get_sym_hash_ena_per_port (port_id)
```

For example, to get symmetric hash enable configuration of port 1:

```
testpmd> get_sym_hash_ena_per_port 1
```

4.8.12 set_sym_hash_ena_per_port

Set symmetric hash enable configuration per port to enable or disable:

```
set_sym_hash_ena_per_port (port_id) (enable|disable)
```

For example, to set symmetric hash enable configuration of port 1 to enable:

```
testpmd> set_sym_hash_ena_per_port 1 enable
```

4.8.13 get_hash_global_config

Get the global configurations of hash filters:

```
get_hash_global_config (port_id)
```

For example, to get the global configurations of hash filters of port 1:

```
testpmd> get_hash_global_config 1
```

4.8.14 set_hash_global_config

Set the global configurations of hash filters:

```
set_hash_global_config (port_id) (toeplitz|simple_xor|default) \
(ipv4|ipv4-frag|ipv4-tcp|ipv4-udp|ipv4-sctp|ipv4-other|ipv6|ipv6-frag| \
ipv6-tcp|ipv6-udp|ipv6-sctp|ipv6-other|l2_payload) \
(enable|disable)
```

For example, to enable simple_xor for flow type of ipv6 on port 2:

```
testpmd> set_hash_global_config 2 simple_xor ipv6 enable
```

4.8.15 set_hash_input_set

Set the input set for hash:

```
set_hash_input_set (port_id) (ipv4-frag|ipv4-tcp|ipv4-udp|ipv4-sctp| \
ipv4-other|ipv6-frag|ipv6-tcp|ipv6-udp|ipv6-sctp|ipv6-other| \
l2_payload) (ovlan|ivlan|src-ipv4|dst-ipv4|src-ipv6|dst-ipv6|ipv4-tos| \
ipv4-proto|ipv6-tc|ipv6-next-header|udp-src-port|udp-dst-port| \
tcp-src-port|tcp-dst-port|sctp-src-port|sctp-dst-port|sctp-veri-tag| \
udp-key|gre-key|fld-1st|fld-2nd|fld-3rd|fld-4th|fld-5th|fld-6th|fld-7th| \
fld-8th|none) (select|add)
```

For example, to add source IP to hash input set for flow type of ipv4-udp on port 0:

```
testpmd> set_hash_input_set 0 ipv4-udp src-ipv4 add
```

4.8.16 set_fdir_input_set

The Flow Director filters can match the different fields for different type of packet, i.e. specific input set on per flow type and the flexible payload. This command can be used to change input set for each flow type.

Set the input set for flow director:

```
set_fdir_input_set (port_id) (ipv4-frag|ipv4-tcp|ipv4-udp|ipv4-sctp| \
ipv4-other|ipv6|ipv6-frag|ipv6-tcp|ipv6-udp|ipv6-sctp|ipv6-other| \
l2_payload) (ivlan|ethertype|src-ipv4|dst-ipv4|src-ipv6|dst-ipv6|ipv4-tos| \
ipv4-proto|ipv4-ttl|ipv6-tc|ipv6-next-header|ipv6-hop-limits| \
tudp-src-port|udp-dst-port|cp-src-port|tcp-dst-port|sctp-src-port| \
sctp-dst-port|sctp-veri-tag|none) (select|add)
```

For example to add source IP to FD input set for flow type of ipv4-udp on port 0:

```
testpmd> set_fdir_input_set 0 ipv4-udp src-ipv4 add
```

4.8.17 global_config

Set different GRE key length for input set:

```
global_config (port_id) gre-key-len (number in bytes)
```

For example to set GRE key length for input set to 4 bytes on port 0:

```
testpmd> global_config 0 gre-key-len 4
```