



**DPDK**

DATA PLANE DEVELOPMENT KIT

**Mempool Device Driver**

*Release 18.11.0*

November 27, 2018

## CONTENTS

<b>1</b>	<b>OCTEON TX FPAVF Mempool Driver</b>	<b>2</b>
1.1	Features . . . . .	2
1.2	Supported OCTEON TX SoCs . . . . .	2
1.3	Prerequisites . . . . .	2
1.4	Pre-Installation Configuration . . . . .	2
1.5	Initialization . . . . .	3

The following are a list of mempool PMDs, which can be used from an application through the mempool API.

## OCTEON TX FPAVF MEMPOOL DRIVER

The OCTEON TX FPAVF PMD (`librte_mempool_octeontx`) is a mempool driver for offload mempool device found in **Cavium OCTEON TX** SoC family.

More information can be found at [Cavium, Inc Official Website](#).

### 1.1 Features

Features of the OCTEON TX FPAVF PMD are:

- 32 SR-IOV Virtual functions
- 32 Pools
- HW mempool manager

### 1.2 Supported OCTEON TX SoCs

- CN83xx

### 1.3 Prerequisites

See `:doc: ../platform/octeontx.rst` for setup information.

### 1.4 Pre-Installation Configuration

#### 1.4.1 Config File Options

The following options can be modified in the `config` file. Please note that enabling debugging options may affect system performance.

- `CONFIG_RTE_MBUF_DEFAULT_MEMPOOL_OPS` ( set to `octeontx_fpavf`)  
Set default mempool ops to `octeontx_fpavf`.
- `CONFIG_RTE_LIBRTE_OCTEONTX_MEMPOOL` (default `y`)  
Toggle compilation of the `librte_mempool_octeontx` driver.

## 1.4.2 Driver Compilation

To compile the OCTEON TX FPAVF MEMPOOL PMD for Linux arm64 gcc target, run the following `make` command:

```
cd <DPDK-source-directory>
make config T=arm64-thunderx-linuxapp-gcc test-build
```

## 1.5 Initialization

The OCTEON TX fpavf mempool initialization similar to other mempool drivers like ring. However user need to pass `--base-virtaddr` as command line input to application example `test_mempool.c` application.

Example:

```
./build/app/test -c 0xf --base-virtaddr=0x100000000000 \
  --mbuf-pool-ops-name="octeontx_fpavf"
```